



More than just doors

P7

Flexibility meets versatility

A swing door for loads of different applications



P7

The universal solution for smooth processes

Great flexibility

With a door leaf made of 7 mm PVC, the single- or double-leaf ZP7 version of the P7 swing door allows for fast-moving and uncomplicated passage of both people or compact forklifts and other industrial vehicles. This makes the P7 especially recommendable for highly frequented areas where a demarcation is required.

Superb hygiene

The P7 door leaf can be cleaned quickly and efficiently and just as easily replaced if necessary. The gallow profile made of corrosion- and acid-resistant chrome-nickel steel disappears into the curtain. The design prevents contamination in the hygienically neutral area of the door leaf suspension.

Practical product diversity

For increased durability, the P7 door leaf is also available with a mesh insert. It is also available in cold-resistant materials (without net insert) for use in below-zero temperature areas. Double PVC is another option for collision protection and increased overall stability. The solid colour PVC door leaf gives this door an individual look and feel for use in a variety of operating environments. The P7 can also be configured for tubular track passages.

One door – loads of applications

The innovative design, robust components and great flexibility make the P7 especially effective in high traffic areas. The P7 is thus ideal for separating spaces and containing the spread of emissions such as dust, fumes or odours without restricting movement.


Impressive in any installation

- Practical space demarcation
- Ideal for high traffic areas
- Resistant and robust
- Efficient and seamless cleaning
- Also available for meat rail through-put
- Available as a double-leaf swing door (ZP7)

Do you have any questions? We have the answers.

Contact us – phone: +49 (0)5422 609-0, E-mail: info@coolit.de

More information is available at: www.coolit.de



1 P7 swing door

2 Leaf suspension with stainless steel oval tube incl. attachment and adjustment

3 Robust leaf made of V2A stainless steel

4 Door leaves made of 7 mm PVC – easy replacement if required

5 Corrosion- and acid-resistant materials and components

Technical data

Application and temperature range

Operating room, cold store (+1 °C to +8 °C), freezer room (0 °C to -28 °C) – no cold/heat insulating effect

Dimensions	P7 (single-leaf)	ZP7 (double-leaf)
Clear width (CW)	minimum: 500 mm, maximum: 1,400 mm	minimum: 1,000 mm, maximum: 2,800 mm
Clear height (CH)	minimum: 800 mm, maximum: 2,800 mm	minimum: 1,800 mm, maximum: 2,800 mm
Special sizes	Special sizes on request	
Leaf thickness (door leaf)	7 mm	

Material

Door leaf

PVC	Transparent soft PVC-P, optional: solid colour soft PVC-P (standard colours similar to RAL): food safe, physiologically harmless, high chemical resistance (including acid and alkali resistance), high impact resistance even at low temperatures
PVC with mesh insert	Transparent soft PVC-P with mesh insert, optional: solid colour soft PVC-P with mesh insert (standard colours similar to RAL): food-safe, physiologically harmless, high chemical resistance (e.g. to acids and alkali), high impact resistance even at low temperatures

Frame

- Masonry installation: stainless steel base plate 142 x 95 x 4 mm, stainless steel flat profile 80 x 4 mm / 80 x 8 mm, stainless steel wraparound frame
- Installation in element (panel): stainless steel U-frame
- Installation behind cool it door

Hinges

cool it hinges made of stainless steel (CNS), V2A (1.4301)

Opening angle 90° on both sides, self-closing, integrated 90° stop (optional: without 90° stop)



Technical data

Special equipment (optional)

Doubling (transparent soft PVC-P, 7 mm thick, on both sides, standard colours similar to RAL)

Meat rail through-put





Double-leaf version (ZP7)

Colour scale

Standard colours similar to RAL (for suspension / loops and doubled leaves).

Colour for suspension / loop: standard similar to RAL 3000 (Flame red), optional: standard colours similar to RAL on request.

Colours shown may differ from the original RAL colours.



If you require further information on equipment options and technical details, cool it will be happy to help.



OPERATING ROOM
COLD STORE
FREEZER ROOM



STURDY
CONSTRUCTION



DURABLE
DESIGN



CERTIFIED
QUALITY



SECURITY
AND
PROTECTION



CERTIFIED



OPTIMAL
HYGIENE



FLEXIBILITY



OPTIONAL
EXTRAS



WIDE RANGE
OF COLOURS

cool it
More than just doors

cool it Isoliersysteme GmbH

Ochsenweg 18
49324 Melle/GERMANY

Phone +49 (0)5422 609-0

Fax +49 (0)5422 609-249

E-mail info@coolit.de

www.coolit.de



www.coolit.de

All information relating to the scope of delivery, appearance, performance characteristics, dimensions, etc. correspond to the information at the time the publication was created. Some of the depicted products in this catalogue are equipped with features that are only available at a surcharge. Presented illustrations or details in such illustrations may differ from the original. All information is supplied without guarantee. Subject to technical and other changes, no responsibility accepted for mistakes or printing errors. All specifications are subject to change without notice.

© 2024 cool it Isoliersysteme GmbH.
All rights reserved.